The 8th International Workshop on

ADVANCED MATERIALS SCIENCE

AND NANOTECHNOLOGY

Ha Long City, Vietnam, 8-12 November, 2016

 Contact Address: IWAMSN 2016 Workshop Secretariat and Administration Staff Institute of Materials Science, Vietnam Academy of Science and Technology, 18 Hoang Quoc Viet Road, Cau Giay District, Hanoi, Vietnam.
Phone: (84-4) 3.7568870
Fax: (84-4) 3.8360705
Email: iwamsn2016@ims.vast.ac.vn
Website: http://www.iwamsn.ac.vn

ABSTRACT FORM

(Submission Deadline: 15 August 2016)

Title:High accuracy electronic compass for detecting azimuth
direction based on a novel magnetoelectric effect

Category

x Oral presentation

Poster presentation

Session:

1. Materials for Electronics and Photonics (code: MEP)

- 2. Nanostructured Materials and Devices (code: NMD)
- 3. Nanotechnology in Life Science and Environment Technology (code: NLE)
- 4. New Materials for Energy (code: NME)
- 5. Two-dimensional Hexagonal Semiconductors (code: THS)
- Author(s): D.T. Huong Giang, N.D. Phuong, P.A. Tuan, N.B. Bien, N.V. Tuan and N.H. Duc
- Institution: VNU Key laboratory for Micro-nano Technologies and Faculty of Physics Engineering and Nanotechnology, VNU University of Engineering and Technology, Vietnam National University, Hanoi, 144 Xuan Thuy Road, Cau Giay, Hanoi, Viet Nam

Speaker: Do Thi Huong Giang and Nguyen Huu Duc

E-mail: giangdth@vnu.edu.vn

Abstract:

Most navigation systems today use compass to determine heading direction based on determining the earth's magnetic fields in a horizontal plane. There are several types of electronic compasses based on different effects such as fluxgate, magnetoresistive, and magnetoinductive. This paper presents a novel electronics compassing for navigation system, a modification of the conventional magnetic compass, which based on magnetoelectric effect. Recent researches have shown that thanks to enhancement of shape magnetic anisotropy of Metglas ribbon, an high magnetic sensitivity (~Voltage/Tesla), and extremely high accurary (1 nanoTesla) geomagnetic sensors based on Metglas/PZT magnetoelectric laminate were built [1]. By intergrating 2-axis sensor with an electronic circuit and 12-bit ADC (Fig. 1), a high resolution magnetoelectric compass heading accuracy. This kind of magnetoelectric compass would contribute to the most sensitive and high accuracy electronic compass available in the industry today.



Fig. 1. Photos of the electronic compass based on magnetoelectric effect (a) and LCD display (b)

[1] D.T. Huong Giang, PA. Duc, N.T. Ngoc, N.H. Duc, Geomagnetic sensors based on Metglas/PZT laminates, *Sensor and Actuator A: Physics*, A179 (2012) 78-82 (SCI), doi:10.1016/j.sna.2012.03.030